

# MATERIAL SAFETY DATA SHEET

AMAZON PAINT  
779 Palmyrita Avenue  
RIVERSIDE, CA 92503  
DATE OF PREPARATION: 12/10/2011

EMERGENCY TELEPHONE NUMBER:  
1-800-262-8200 CHEMTREC  
INFORMATION TELEPHONE NUMBER:  
(951) 588-0206

## SECTION I -PRODUCT IDENTIFICATION

MSDS FORM H: HMIS CODES: H F R PP  
1 0 0 E

AMAZON SELECT – INTERIOR/EXTERIOR RECYCLED LATEX PAINT

(SEE COVER PAGE FOR LIST OF PRODUCTS COVERED)

U.S. DOT SHIPPING DESCRIPTION:(Non-Regulated)

## SECTION II -HAZARDOUS INGREDIENTS

INGREDIENT	CAS NUMBER	%WT	PPM	ACGIH OSHA EXPOSURE LIMITS			VAPOR PRESS mmHg @ temp
				TLV/TWA	TWA <sup>3</sup>	STEL <sup>3</sup>	
Ethylene Glycol	00107-21-1	0-5%	-	-	-	50 125	0.1 @ 68 F
Propylene Glycol	00057-55-6	0-5%	-	-	-	-	0.1 @ 68 .F
Texanol Ester Alcohol	25265-77-4	0-5%	-	-	-	-	0.1 @ 68 .F F

NOTE: This product consists primarily of post-consumer recyclable latex paints that were produced by various manufacturers. Composition of finished product may vary with feedstocks.

## SECTION III -PHYSICAL AND CHEMICAL DATA

BOILING RANGE: 200-225.F EVAPORATION RATE: Slower Than Ether.  
SPECIFIC GRAVITY (H2O=1): 1.4 VAPOR DENSITY: Heavier Than Air.  
SOLUBILITY IN WATER: Partly soluble. VOLATILE VOLUME: 60%  
APPEARANCE AND ODOR: Liquid dispersion with mild odor.

## SECTION IV -FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: N/A  
FLASH POINT: N/A LEL: N/A UEL: N/A  
EXTINGUISHING MEDIA: Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog.  
UNUSUAL FIRE AND EXPLOSION HAZARDS: Liquid material is non-combustible, but dried films are capable of supporting combustion when in contact with open flames. Closed containers can develop internal pressure and may rupture when subjected to extreme heat.  
SPECIAL FIREFIGHTING PROCEDURES: Use self-contained breathing apparatus in confined spaces. Observe recommended procedures for handling ordinary combustible materials.

## SECTION V -HEALTH HAZARD DATA

### POTENTIAL ROUTES OF ENTRY / SIGNS AND SYMPTOMS OF EXPOSURE

**INHALATION:** Exposure to high vapor concentration may irritate mucous membranes and respiratory tract. Extreme overexposure may produce dizziness, headache, and nausea.

**EYE CONTACT:** Direct contact may cause eye irritation, redness, and tearing.

**SKIN CONTACT:** Prolonged contact may cause transient reddening of the skin.

**SKIN ABSORPTION:** Available information provides no evidence of adverse effects.

**INGESTION:** May cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** Pre-existing eye, skin, and respiratory system disorders, and unusual allergic sensitivity.

**CHRONIC OR DELAYED HEALTH HAZARDS:** Available information provides no evidence of chronic or delayed health hazards associated with exposure to this product.

**CARCINOGENICITY:** NTP? NO. IARC MONOGRAPHS? NO. OSHA REGULATED? NO. PROP 65? NO.

**MSDS FORM H:** AMAZON SELECT – INTERIOR/EXTERIOR RECYCLED LATEX PAINT, PAGE 2

**EMERGENCY AND FIRST AID PROCEDURES:** If affected by inhalation of vapor, move victim to fresh air. If not breathing, apply artificial respiration and call emergency medical care. For eye contact, flush eyes with fresh water for at least 15 minutes. If irritation persists, seek medical attention. For skin contact, wash thoroughly with soap and water. Remove any contaminated clothing. If swallowed, have victim drink enough fresh water to ensure dilution. Call emergency medical care.

### SECTION VI -REACTIVITY DATA

**STABILITY:** Stable. **HAZARDOUS POLYMERIZATION:** Will not occur.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Combustion can produce carbon monoxide and/or carbon dioxide.

**CONDITIONS TO AVOID:** Avoid storage or use at temperatures below 40.F. Avoid freezing.

**INCOMPATIBILITY (MATERIALS TO AVOID):** Avoid water-reactive materials, strong oxidizers, acids and alkalis.

### SECTION VII -PRECAUTIONS FOR SAFE HANDLING, STORAGE, AND DISPOSAL

**PRECAUTIONS FOR HANDLING AND STORAGE:** Keep containers closed when not in use. Do not handle or store near heat, flame, or strong oxidizers, acids and alkalis. Store in cool, well-ventilated area. Rotate stock, use older material first. Inspect all containers for leaks.

**STEPS TO TAKE IF MATERIAL IS RELEASED OR SPILLED:** Dike and absorb spilled liquid with inert material such as clay granules, sand, earth, or sawdust. Use rags to clean up small amounts of spilled material.

### SECTION VIII -CONTROL MEASURES FOR SAFE USE

**WASTE DISPOSAL METHOD:** Collect contaminated absorbent material and rags into a suitable container and dispose in accordance with all applicable local, state, and federal regulations.

**RESPIRATORY PROTECTION:** For spray application, use particulate filter mask to avoid breathing spray mist. Exposed persons with unusual allergic sensitivity may need organic vapor respirator (NIOSH/MSHA TC 23C or equivalent).

**VENTILATION:** For interior use, general mechanical ventilation may be sufficient to disperse vapor. Otherwise, open doors and windows or use portable fans to provide local exhaust.

**EYE PROTECTION:** Use safety glasses, goggles, or face shield to protect eyes.

**PROTECTIVE GLOVES:** Use waterproof gloves (e.g., latex, vinyl, rubber, neoprene) to avoid skin contact.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Waterproof head covering and general protective clothing are recommended for protection as necessary.

WORK/HYGIENIC PRACTICES: Wash hands and face before eating.

SECTION IX -SPECIAL CAUTIONS

Do not store in areas subject to freezing temperatures. Keep above 40.F at all times. Use only with adequate ventilation or protection. Avoid breathing spray mist or vapor. Do not ingest. Avoid contact with skin. Close container after each use. Keep out of reach of children.

SECTION X -TRANSPORTATION INFORMATION

Shipping Requirements: Products covered by this MSDS are not subject to DOT, IATA/ICAO, or IMO/IMDG transportation regulations. Acceptable for air transport as non-hazardous goods.

\*\*\*\*\* DISCLAIMER \*\*\*\*\*

THE INFORMATION CONVEYED ABOVE, ALTHOUGH OBTAINED FROM SOURCES WE CONSIDER RELIABLE, IS FURNISHED BY AMAZON ENVIRONMENTAL INC. WITHOUT ANY WARRANTY (WHETHER EXPRESS OR IMPLIED) AS TO ITS ACCURACY, ADEQUACY, OR APPLICABILITY TO ANY PARTICULAR NEEDS OR CIRCUMSTANCES.

